



I&J Mfg. also manufactures
Crop Rollers, Cultivators
and Forecarts.

10 S New Holland Rd, Suite 2
Gordonville, PA 17529
717-442-9451
i-jmanufacturing.com

I&
mfg.
J

10 S New Holland Rd, Suite 2
Gordonville, PA 17529

I&
mfg.
J

2025

3RD QUARTER
NEWSLETTER



Introducing the
*New Twin Blade
Mower!*

Mowers Experience clean cutting for faster regrowth and virtually ZERO plugging.



- Two cutter bars provide extra wide cutting swath.
- Powered by PTO or engine.
- Hydraulics enable operator to easily move into transport mode of 102" wide.
- Rear wheels are steered by hydraulics from the driver's seat for easy maneuverability.
- Non plugging, clean cut.

706 MOWER SPECS:

Specifications	706 Twin Blade
Overall Width When Working	312"
Transport Width	102"
Transport Height	130"
Length Front to Back	228"
PTO Horse Power Required	25
PTO Output Shaft	No
Power Transmission	3 - A-series belts
Hydraulics Required	3 Hose Hookup
Weight (Approx.)	2450 lbs.
Shipping Dimensions	228" x 102" x 48"

I&J manufactures a quality line of sickle bar mowers for *both* tractor and horse farmers.

Be sure to check them out at I-Jmanufacturing.com.

MOWER FEATURES:

- Heat-treated blades and drive system made by ESM in Germany.
- Lightweight.
- Low torque required (can even be ground drive).
- Three-point hitch or tailing for tractor, cart or draft hitch.
- Can operate from 90 degrees to 30 degrees down
- Working widths of 5 1/2, 7, 8 or 9 ft.
- Includes a safety release with automatic re-hooking to help protect against damage to the cutter bar when coming in contact with objects, such as a fence, etc.
- Built for gasoline engine, PTO or ground drive.
- Retro-fit kit available to convert other mowers.



10 S New Holland Rd, Suite 2
Gordonville, PA 17529
717-442-9451
i-jmanufacturing.com